SYTRACK BIHM MEDICAL

BIHM MEDICAL

5.45 kg / 12 lb / 0.86 st 200 kg / 440 lb / 31.49 st

Portable Ceiling Lift Voyager

BHM Medical's 12-pound portable track lift, the Voyager, is a David in a world of Goliaths. Not only is it easy to carry and store, but with a lifting capacity of some 440 pounds, it is in a performance class by itself. With its 24-volt battery pack, it can be recharged in less than 2 hours. Now BHM has added the "Quick Releaser", a user-friendly device which swiftly disengages the strap for easy, safe and quick suspension and removal of the lift.

The Voyager portable offers a lifting capacity of : 440 lb (200 kg)

	0			
10.00		and the second		
1	An			
1		ST PARA		
V				
				1
# F	Product	Description	Market	
VO	YAGER	Voyager - 2 ways	North Am	erica
9800008		Voyager - 2 ways	Europe & United Kingdom	
				nguom
			C <u></u>	
			VOYAGER	9800008
	# Part	Description	8	980
		Hand Control - 2 Way	•	•
1	700.13600			•
2	A8500	Battery Pack	•	
	A8500 700.13500		•	•
2	A8500	Battery Pack	•	•
2 3	A8500 700.13500	Battery Pack Battery Charger	•	•



Suggested Slings / Harness / Stretchers
Total support/ Stand position
Partial support/ Stand position

Band √ Walking

Chest

√ Limb sling

Total transfer

Partial support/ Lay-down position

700.10620

Repositioning

√ Hammock /Hammonk 6

Universal stretcher

Morgue

√ Quick Fit

√ Hygienic

√ Combi Bariatric Total support/ Lay-down position

	Linung	oupdoily	Loo ng r r ro io r o n ro o c			
	Soft st	art & stop movement				
	Return to charge function on handset					
	Safet	y Features				
	Emerg	ency lowering device	Manual			
		e for emergency stop of the mechanism	Helps to prevent freefalls			
	Current limiter & emergency stopping device					
		nical Specifications				
		D 2601-1 / ISO 10535 / CSA C22.2 No. 601.1				
		al displacement speed	4 cm/sec (1.6 in/sec)			
		ry Specifications				
		rgeable sealed lead acid	24VDC, 2.0Ah			
		ent & fast charging system	2 to 4 hrs for complete charge			
		y capacity with load of / 180 lb / 12.6 st	Up to 30 transfers			
	Low b	attery disconnect system	Protect batteries from been drained			
	Charge input – 90-240 Vac, 50-60 Hz, 27VA max.					
	Charg	e indicator	Visual			
	Strap Specifications					
	Length	1	2,2 m (88 in)			
	Autom					
	Unit Construction					
	Frame – aluminium					
	Cover – fire retardant plastic					
	6	6 %	8			
Q	a					
a	Ca.	٥ 💊 ٥				
1		A LI II I	1 1 80			
e						
			0			
		1				
	Acce	ssories				
	а	700.10650	Trolley KWIKtrak			
	а	A5900	Trolley BHM track			
	b	A3710	A discrimination of the strength of the streng			
		70710	Adjustable extension strap - Blue			
	c1	700.08310	Adjustable extension strap - Blue Reacher 61 cm / 24"			
	c1 c2					
		700.08310	Reacher 61 cm / 24"			
	c2	700.08310 700.08320	Reacher 61 cm / 24" Reacher 91 cm / 36"			
	c2 d	700.08310 700.08320 A5720	Reacher 61 cm / 24* Reacher 91 cm / 36* Trapeze			
	c2 d e	700.08310 700.08320 A5720 A5710	Reacher 61 cm / 24* Reacher 91 cm / 36* Trapeze Trapeze with hook 41 cm (16 in) Scale Unit and adaptor / 350 kg (770 lb)			
1	c2 d e f	700.08310 700.08320 A5720 A5710 700.05720	Reacher 61 cm / 24* Reacher 91 cm / 36* Trapeze Trapeze with hook 41 cm (16 in) Scale Unit and adaptor / 350 kg (770 lb) (North America)			
	c2 d e f g	700.08310 700.08320 A5720 A5710 700.05720 700.05740	Reacher 61 cm / 24* Reacher 91 cm / 36* Trapeze Trapeze with hook 41 cm (16 in) Scale Unit and adaptor / 350 kg (770 lb) (North America) Spreader bar			

Features Weight

Lifting capacity

0

6

4

Swivel Trolley for portable